



XI'AN FUNCTION MATERIAL GROUP CO., LTD  
Material Safety Data Sheet  
Titanium Silicon Alloy

---

1. Product and Company Identification

---

Trade Name: Titanium silicon alloy  
Chemical Formula: Ti-Si  
Recommended Use: Scientific research and development

Manufacturer/Supplier: XI'AN FUNCTION MATERIAL GROUP CO., LTD  
Street: No. 69, Gazelle Valley, High-Tech Zone  
City: XI'AN  
State: Shannxi  
Zip Code: 710077  
Country: China  
Tel #: +86-29-88993870/+86-13519132051

---

2. Hazards Identification

---

Signal Word: Warning



Hazard Statements: H228 Flammable solid - powder  
H315 Causes skin irritation  
H319 Causes serious eye irritation

Precautionary Statements: P210 Keep powder away from heat/spark/flame. No smoking.  
P261 Avoid breathing dust/fume/vapor  
P305+P351 If in eyes: Rinse cautiously with water for several minutes.

HMIS Health Ratings (0-4): Powder Pieces or higher

Health:	1	1
Flammability:	2	0
Physical:	2	1

---

3. Composition

---

Chemical Family: Intermetallic compound  
Additional Names: Titanium silicide

Titanium (Ti):  
Percentage: 0-100 wt%  
CAS #: 7440-32-6  
EC #: 231-142-3

Silicon (Si):  
Percentage: 0-100 wt%  
CAS #: 7440-21-3  
EC #: 231-130-8

---

#### 4. First Aid Procedures

---

General Treatment:	Seek medical attention if symptoms persist.
Special Treatment:	None
Important Symptoms:	None
Inhalation:	Remove victim to fresh air. Supply oxygen if breathing is difficult.
Ingestion:	Give one to two glasses of water and induce vomiting. Never induce vomiting or give anything by mouth to an unconscious person.
Skin:	Wash affected area with mild soap and water. Remove any contaminated clothing.
Eyes:	Flush eyes with water, blinking often for several minutes. Remove contact lenses if present and easy to do. Continue rinsing

---

#### 5. Firefighting Measures

---

Flammability:	Non-flammable, except as powder
Extinguishing Media:	Do not use water for metal fires – use CO <sub>2</sub> , sand, extinguishing powder.
Spec. Fire Fighting Procedure:	Use full-face, self-contained breathing apparatus with full protective clothing to prevent contact with skin and eyes. See section 10 for decomposition products.

---

#### 6. Accidental Release Measures

---

If Material Is Released/Spilled:	Wear appropriate respiratory and protective equipment specified in special protection information. Isolate spill area and provide ventilation. Vacuum up spill using a high efficiency particulate absolute (HEPA) air filter and place in a closed container for disposal. Take care not to raise dust.
Environmental Precautions:	Isolate runoff to prevent environmental pollution.

---

#### 7. Handling and Storage

---

Handling Conditions:	Wash thoroughly after handling.
Storage Conditions:	Store in a cool dry place in a tightly sealed container. Store apart from materials and conditions listed in section 10.
Work/Hygienic Maintenance:	Do not use tobacco or food in work area. Wash thoroughly before eating and smoking. Do not blow dust off clothing or skin with compressed air.
Ventilation:	Provide sufficient ventilation to maintain concentration at or below threshold limit.

---

#### 8. Exposure Controls and Personal Protection

---

Permissible Exposure Limits:	None
Threshold Limit Value:	None
Special Equipment:	None
Respiratory Protection:	Dust Respirator
Protective Gloves:	Rubber gloves
Eye Protection:	Safety glasses or goggles
Body Protection:	Protective work clothing. Wear close-toed shoes and long sleeves/pants.

---

## 9. Physical and Chemical Characteristics

---

Color	Grey
Form:	Powder, Granules, Pellets, Sputtering target, Custom parts
Odor:	Odorless
Water Solubility:	Insoluble
Boiling Point:	N/A
Melting Point:	N/A
Flash Point:	N/A
Autoignition Temperature:	N/A
Density:	N/A
Molecular weight:	N/A

---

## 10. Reactivity

---

Stability:	Stable under recommended storage conditions
Reacts With:	Oxidizing agents, Bases
Incompatible Conditions:	None
Hazardous Decomposition Products:	Metal oxide fume

---

## 11. Toxicological Information

---

Potential Health Effects:	
Eyes:	May cause serious irritation
Skin:	May cause irritation
Ingestion:	May cause irritation
Inhalation:	May cause irritation
Chronic:	Inorganic silicon compounds may be acute inhalation irritants. Prolonged inhalation may cause pulmonary fibrosis known as silicosis. Titanium compounds are considered physiologically inert. There are no reported cases in the literature where titanium as such has caused human intoxication
Signs & Symptoms:	N/A
Aggravated Medical Conditions:	N/A
Median Lethal Dose:	N/A
Carcinogen:	N/A

---

## 12. Ecological Information

---

Aquatic Toxicity:	Low
Persistent Bioaccumulation Toxicity:	No
Very Persistent, Very Bioaccumulative:	No
Notes:	N/A

---

## 13. Disposal Considerations

---

Dispose of in accordance with local, state, national, and international regulations.

---

#### 14. Transportation Data

---

Hazardous: Hazardous as powder only.



Hazard Class: 4.1 Flammable solids  
Packing Group: III  
UN Number: UN3178  
Proper Shipping Name: Flammable solid, inorganic, n.o.s. (Titanium silicide)

---

#### 15. Regulatory Information

---

Sec 302 Extremely Hazardous: No  
Sec 304 Reportable Quantities: N/A  
Sec 313 Toxic Chemicals: No

---

#### 16. Other Information

---

This safety data sheet should be used in conjunction with technical sheets. It does not replace them. The information given is based on our knowledge of this product, at the time of publication. It is given in good faith. The attention of the user is drawn to the possible risks incurred by using the product for any other purpose other than that for which it was intended. This does not in any way excuse the user from knowing and applying all the regulations governing his activity. It is the sole responsibility of the user to take all precautions required in handling the product. The aim of the mandatory regulations mentioned is to help the user to fulfill his obligations regarding the use of hazardous products.

Document Last Revised: 09/22/2015